



FICHA TÉCNICA

Referencias: 09512153; 09512154; 09512155; 09512156; 09512157; 09512158; 09512159; 09512160; 09512161; 09512162; 09512164; 09512165; 09512166; 09512167; 09512168; 09512169; 09512170; 09512171; 09512172; 09512173; 09512174; 09512175

Llave fija de golpe | En medidas desde la SW 24 hasta la SW 120 | Fabricada en acero al cromo vanadio extrafuerte



cofan

Llave de golpe negra fija una boca.

Medidas desde sw 24 hasta sw 120.

Para montajes especialmente difíciles y con altas exigencias de par de apriete.


Fabricada en acero Cromo vanadio fosfatado de alta resistencia.

Frecuente y solicitada en los talleres mecánicos, esta llave de impacto reducirá sus esfuerzos para aflojar y apretar tuercas o tornillos.

Para montajes especialmente difíciles y con altas exigencias de par de apriete



FICHA TÉCNICA

Ref	M	
0951 2153	24	1
0951 2154	27	1
0951 2155	30	1
0951 2156	32	1
0951 2157	36	1
0951 2158	41	1
0951 2159	46	1
0951 2160	50	1
0951 2161	55	1
0951 2162	60	1
0951 2164	65	1
0951 2165	70	1
0951 2166	75	1
0951 2167	80	1
0951 2168	85	1
0951 2169	90	1
0951 2170	95	1
0951 2171	100	1
0951 2172	105	1
0951 2173	110	1
0951 2174	115	1
0951 2175	120	1



FICHA TÉCNICA

referencia	boca	L	A	B	C	peso [kg]
0951 2153	24	150	24	50	12	0.4
0951 2154	27	175	27	60	15	
0951 2155	30	190	30	65	16	0.6
0951 2156	32		32			
0951 2157	36	210	36	75	17	0.7
0951 2158	41	230	41	90	18	0.8
0951 2159	46	250	46	100	20	1.5
0951 2160	50	280	50	110	21	2.0
0951 2161	55	300	55	120	23	
0951 2162	60	320	60	130		23
0951 2164	65	340	65	140	28	5.0
0951 2165	70	370	70	160	29	
0951 2166	75	380	75			29
0951 2167	80	400	85	175	32	7.0
0951 2168	85					
0951 2169	90	450	95	195	36	10
0951 2170	95					11
0951 2171	100	490	105	230	43	14
0951 2172	105					
0951 2173	110	500	115	230	45	19
0951 2174	115					
0951 2175	120					

MATERIAL	Cromo Vanadio
DUREZA	de 17mm a 46mm: 34 – 40 HRC de 50mm a 150mm: 30 – 36 HRC
ACABADO	Fosfatado

