



DADOS TÉCNICOS

Referência: 093305110; 093305160; 093306115; 093306165; 093306215; 093306265; 093308115; 093308165; 093308215; 093308315; 093308465; 093310110; 093310165; 093310215; 093310315; 093310465; 093312165; 093312215; 093312315; 093312465; 093314215; 093314315; 093314465; 093316315; 093316465; 093318450; 093320450; 093322450; 093324450; 093325450

Brocas para betão armado SDS PLUS com ponta compacta e reforçada | Ideal para betão armado | Diferentes tamanhos à escolha



Brocas para betão e betão armado com uma ponta compacta e reforçada e 4 arestas de corte.

Esta broca é adequada para percussão e rotação.
Oferece uma vida útil mais longa, maior desempenho e mais material removido.
Inclui âncora SDS PLUS.

Os tamanhos incluídos nesta gama vão de 5 a 25 milímetros de diâmetro e comprimentos de 110 a 465 milímetros.



DADOS TÉCNICOS



REFORÇADO

Ref	Ø	↔	P		
0933 05110	5 mm	115 mm	50 mm	1	✓
0933 05160	5 mm	165 mm	100 mm	1	✓
0933 06115	6 mm	115 mm	50 mm	1	✓
0933 06165	6 mm	165 mm	100 mm	1	✓
0933 06215	6 mm	215 mm	150 mm	1	✓
0933 06265	6 mm	265 mm	200 mm	1	✓
0933 08115	8 mm	115 mm	50 mm	1	✓
0933 08165	8 mm	165 mm	100 mm	1	✓
0933 08215	8 mm	215 mm	150 mm	1	✓
0933 08315	8 mm	315 mm	250 mm	1	✓
0933 08465	8 mm	465 mm	400 mm	1	✓
0933 10110	10 mm	115 mm	50 mm	1	✓
0933 10165	10 mm	165 mm	100 mm	1	✓
0933 10215	10 mm	215 mm	150 mm	1	✓
0933 10315	10 mm	315 mm	250 mm	1	✓
0933 10465	10 mm	465 mm	400 mm	1	✓
0933 12165	12 mm	165 mm	100 mm	1	✓
0933 12215	12 mm	215 mm	150 mm	1	✓
0933 12315	12 mm	315 mm	250 mm	1	✓
0933 12465	12 mm	465 mm	400 mm	1	✓
0933 14215	14 mm	215 mm	150 mm	1	✓
0933 14315	14 mm	315 mm	250 mm	1	✓
0933 14465	14 mm	465 mm	400 mm	1	✓
0933 16315	16 mm	315 mm	250 mm	1	✓
0933 16465	16 mm	465 mm	400 mm	1	✓
0933 18450	18 mm	450 mm	400 mm	1	✓
0933 20450	20 mm	450 mm	400 mm	1	✓
0933 22450	22 mm	450 mm	400 mm	1	✓
0933 24450	24 mm	450 mm	400 mm	1	✓
0933 25450	25 mm	450 mm	400 mm	1	✓