



CARACTÉRISTIQUES TECHNIQUES

Référence: 09731000R; 09731050R; 09731100R; 09731150R; 09731200R; 09731250R; 09731300R; 09731350R; 09731400R; 09731450R; 09731500R; 09731550R; 09731600R; 09731650R; 09731700R; 09731750R; 09731800R; 09731850R; 09731900R; 09731950R; 09732000R; 09732100R; 09732150R; 09732250R; 09732300R; 09732350R; 09732400R; 09732450R; 09732500R; 09732050R; 09732200R

Forets HSS-DIN 338 N Queue réduite

HSS



ES Broca en acero rápido rectificada y punta de 118° afiladas. Mango reducido.

FR Foret en acier rapide rectifié et embout de 118° effilage normal. Embout réduit.

EN Ground twist drills, made from fast steel, 118° sharp point. Reduced shank.

IT Punta in acciaio rapido, rettificato. Punta da 118°, affilata. Gambo ridotto.

PT Broca em aço rápida retificada e ponta de 118°, aguçadas. Haste reduzida.



Forets rectifiés HSS à queue réduite DIN 338N 118°.

Pour l'acier et le fer.
Couleur noire



CARACTERÍSTICAS TÉCNICAS

Ref	Ø		
0973 1000R	10,0 mm	8 mm	1
0973 1050R	10,5 mm	8 mm	1
0973 1100R	11,0 mm	8 mm	1
0973 1150R	11,5 mm	8 mm	1
0973 1200R	12,0 mm	8 mm	1
0973 1250R	12,5 mm	8 mm	1
0973 1300R	13,0 mm	10 mm	1
0973 1350R	13,5 mm	10 mm	1
0973 1400R	14,0 mm	10 mm	1
0973 1450R	14,5 mm	10 mm	1
0973 1500R	15,0 mm	10 mm	1
0973 1550R	15,5 mm	10 mm	1
0973 1600R	16,0 mm	12 mm	1
0973 1650R	16,5 mm	12 mm	1
0973 1700R	17,0 mm	12 mm	1
0973 1750R	17,5 mm	12 mm	1

Ref	Ø		
0973 1800R	18,0 mm	12 mm	1
0973 1850R	18,5 mm	12 mm	1
0973 1900R	19,0 mm	12 mm	1
0973 1950R	19,5 mm	12 mm	1
0973 2000R	20,0 mm	13 mm	1
0973 2050R	20,5 mm	13 mm	1
0973 2100R	21,0 mm	13 mm	1
0973 2150R	21,5 mm	13 mm	1
0973 2200R	22,0 mm	13 mm	1
0973 2250R	22,5 mm	13 mm	1
0973 2300R	23,0 mm	13 mm	1
0973 2350R	23,5 mm	13 mm	1
0973 2400R	24,0 mm	13 mm	1
0973 2450R	24,5 mm	13 mm	1
0973 2500R	25,0 mm	13 mm	1