



CARACTÉRISTIQUES TECHNIQUES

Référence: 10201001; 10201002; 10201003; 10201004; 10201005; 10201006; 10201007; 10201008; 10201009; 10201010; 10201011; 10201012; 10201013; 10201014; 10201015; 10201016; 10201017; 10201018; 10201019; 10201020; 10201021; 10201022; 10201023; 10201024; 10201025; 10201026; 10201027; 10201028; 10201029; 10201030; 10201031; 10201032; 10201033

Meules pour machines à rectifier

Meules « couleur grise » (acier de construction, aciers alliés, fonte grise, etc.) pour les travaux de meulage grossier à la meuleuse.

Grains de G-36 à G-80.

Diamètres de 125 mm à 250 mm.

Epaisseurs de 16mm à 30mm.

Ref	■	Ø	⊙	MODEL	📦
1020 1001	16 mm	125 mm	32 mm	G-36	1
1020 1002	20 mm	125 mm	32 mm	G-36	1
1020 1003	16 mm	150 mm	32 mm	G-36	1
1020 1004	20 mm	150 mm	32 mm	G-36	1
1020 1005	20 mm	180 mm	32 mm	G-36	1
1020 1006	25 mm	180 mm	32 mm	G-36	1
1020 1007	20 mm	200 mm	32 mm	G-36	1
1020 1008	25 mm	200 mm	32 mm	G-36	1
1020 1009	30 mm	200 mm	32 mm	G-36	1
1020 1010	25 mm	250 mm	25 mm	G-36	1
1020 1011	30 mm	250 mm	25 mm	G-36	1
1020 1012	16 mm	125 mm	32 mm	G-60	1
1020 1013	20 mm	125 mm	32 mm	G-60	1
1020 1014	16 mm	150 mm	32 mm	G-60	1
1020 1015	20 mm	150 mm	32 mm	G-60	1
1020 1016	20 mm	180 mm	32 mm	G-60	1
1020 1017	25 mm	180 mm	32 mm	G-60	1
1020 1018	20 mm	200 mm	32 mm	G-60	1
1020 1019	25 mm	200 mm	32 mm	G-60	1
1020 1020	30 mm	200 mm	32 mm	G-60	1
1020 1021	25 mm	250 mm	25 mm	G-60	1
1020 1022	30 mm	250 mm	25 mm	G-60	1
1020 1023	16 mm	125 mm	32 mm	G-80	1
1020 1024	20 mm	125 mm	32 mm	G-80	1
1020 1025	16 mm	150 mm	32 mm	G-80	1
1020 1026	20 mm	150 mm	32 mm	G-80	1
1020 1027	20 mm	180 mm	32 mm	G-80	1
1020 1028	25 mm	180 mm	32 mm	G-80	1
1020 1029	20 mm	200 mm	32 mm	G-80	1
1020 1030	25 mm	200 mm	32 mm	G-80	1
1020 1031	30 mm	200 mm	32 mm	G-80	1
1020 1032	25 mm	250 mm	25 mm	G-80	1
1020 1033	30 mm	250 mm	25 mm	G-80	1

