



## CARACTÉRISTIQUES TECHNIQUES

Référence: 103411516; 103411516-U; 103411524; 103411524-U; 103411536; 103411536-U; 103411560; 103411560-U; 103411580; 103411580-U; 1034115120; 1034115120-U; 103412516; 103412516-U; 103412524; 103412524-U; 103412536; 103412536-U; 103412560; 103412560-U; 103412580; 103412580-U; 1034125120; 1034125120-U; 103418016; 103418016-U; 103418024; 103418024-U; 103418036; 103418036-U; 103418060; 103418060-U; 103418080; 103418080-U; 1034180120; 1034180120-U

### Disque abrasif semi-flexible

Disque abrasif semi-flexible pour la pierre, le marbre, le granit, le terrazzo, le béton, la céramique. Longue durée de vie.

Les disques semi-flexibles nécessitent des patins d'appui sur les meuleuses d'angle.

Différents matériaux : granit/pierre.

Différentes tailles de diamètre.



| Ref         | Ø      |       |    |
|-------------|--------|-------|----|
| 1034 11516  | 115 mm | G-16  | 25 |
| 1034 11524  | 115 mm | G-24  | 25 |
| 1034 11536  | 115 mm | G-36  | 25 |
| 1034 11560  | 115 mm | G-60  | 25 |
| 1034 11580  | 115 mm | G-80  | 25 |
| 1034 115120 | 115 mm | G-120 | 25 |
| 1034 12516  | 125 mm | G-16  | 25 |
| 1034 12524  | 125 mm | G-24  | 25 |
| 1034 12536  | 125 mm | G-36  | 25 |
| 1034 12560  | 125 mm | G-60  | 25 |
| 1034 12580  | 125 mm | G-80  | 25 |
| 1034 125120 | 125 mm | G-120 | 25 |
| 1034 18016  | 178 mm | G-16  | 25 |
| 1034 18024  | 178 mm | G-24  | 25 |
| 1034 18036  | 178 mm | G-36  | 25 |
| 1034 18060  | 178 mm | G-60  | 25 |
| 1034 18080  | 178 mm | G-80  | 25 |
| 1034 180120 | 178 mm | G-120 | 25 |

