




FICHA TÉCNICA

Artículo : 0126
TORNILLO TIRAFONDOS ZINCADO, DIN-571, HEXAGONAL



Diámetro		5	6	7	8	10	12	14	16
Paso		2.00	2.50	3.00	3.50	4.00	4.50	5.00	6.00
s	max.	8.00	10.00	12.00	13.00	17.00	19.00	22.00	24.00
	min.	7.64	9.64	10.57	12.57	16.57	18.57	21.16	23.16
Nueva Norma NF E 25-607	k max.	3.50	4.00	5.00	5.50	7.00	8.00	9.30	10.00
	k min.	3.12	3.62	4.62	4.92	5.95	7.05	8.35	9.25
Antigua Norma NF E 27-140	k max.	4.10	4.60	5.60	6.10	7.80	8.80	9.80	10.80
	k min.	3.20	3.70	4.70	5.20	6.60	7.60	8.60	9.60
r	≈	0.40	0.50	0.80	1.00	1.00	1.20	1.40	1.60
e	min.	8.60	10.80	11.90	14.20	17.50	19.80	22.70	26.10
ds	min.	5.00	6.00	7.00	8.00	10.00	12.00	14.00	16.00
	max.	4.52	5.52	6.42	7.42	9.42	11.30	13.30	15.30
l		b + 20%							
		+ 0 %							
25		15	15						
30		18	18	18	18				
35		21	21	21	21				
40		24	24	24	24	24			
45			27	27	27	27			
50			30	30	30	30	30		
55			33		33				
60			36	36	36	36	36		
65					40				
70			43	43	43	43	43		
80			47	47	47	47	47	47	
90			50		50	50	50		50
100					53	53	53	53	53
120					60	60	60	60	60
130						63			
140					67	67	67	67	67
150					70				
160						73	73	73	73
180							80	80	80