






FICHA TÉCNICA

**Tornillo hexagonal rosca parcial zincado
Con tuerca hexagonal din 934.**

DIN 931/934

Referencia: 0017 + Medida

BAJA RESISTENCIA



Size	b			s		e	k		ds	
	(1)	(2)	(3)	min	max		min	max	min	max
M3	12	-	-	5.32	5.5	6.01	1.88	2.12	2.86	3
M4	14	-	-	6.78	7	7.66	2.68	2.92	3.82	4
M5	16	22	-	7.78	8	8.79	3.35	3.65	4.82	5
M6	18	24	-	9.78	10	11.05	3.85	4.15	5.82	6
(M7)	20	26	-	10.73	11	12.12	4.65	4.95	6.78	7
M8	22	28	-	12.73	13	14.38	5.15	5.45	7.78	8
M10	26	32	45	16.73	17	18.9	6.22	6.58	9.78	10
M12	30	36	49	18.67	19	21.1	7.32	7.68	11.73	12
(M14)	34	40	53	21.67	22	24.49	8.62	8.98	13.73	14
M16	38	44	57	23.67	24	26.75	9.82	10.18	15.73	16
(M18)	42	48	61	26.67	27	30.14	11.28	11.72	17.73	18
M20	46	52	65	29.67	30	33.53	12.28	12.72	19.67	20
(M22)	50	56	69	31.61	32	35.72	13.78	14.22	21.67	22
M24	54	60	73	35.38	36	39.98	14.78	15.22	23.67	24
(M27)	60	66	79	40	41	45.2	16.65	17.35	26.48	27
M30	66	72	85	45	46	50.85	18.28	19.12	29.48	30
(M33)	72	78	91	49	50	55.37	20.58	21.42	32.38	33
M36	78	84	97	53.38	55	60.79	22.08	22.92	35.38	36
(M39)	84	90	103	58.8	60	66.44	24.58	25.42	38.38	39

Size	s		e	m	
	min	max		min	max
M2	3.82	4	4.32	1.35	1.6
M2.5	4.82	5	5.45	1.75	2
M3	5.32	5.5	6.01	2.15	2.4
(M3.5)	5.82	6	6.58	2.55	2.8
M4	6.78	7	7.66	2.9	3.2
M5	7.78	8	8.79	3.7	4
M6	9.78	10	11.05	4.7	5
M7	10.73	11	12.12	5.2	5.5
M8	12.73	13	14.38	6.14	6.5
M10	16.73	17	18.9	7.64	8
M12	18.67	19	21.1	9.64	10
(M14)	21.67	22	24.49	10.3	11
M16	23.67	24	26.75	12.3	13
(M18)	26.16	27	29.56	14.3	15
M20	29.16	30	32.95	14.9	16
(M22)	31	32	35.03	16.9	18
M24	35	36	39.55	17.7	19
(M27)	40	41	45.2	20.7	22
M30	45	46	50.85	22.7	24
(M33)	49	50	55.37	24.7	26
M36	53.8	55	60.79	27.4	29
(M39)	58.8	60	66.44	29.4	31

- (1) For $L \leq 125\text{mm}$
 (2) For $125 < L \leq 200\text{mm}$
 (3) For $L > 200\text{mm}$